Zigpac

Contact Methods
Mob: (86)18668768846
Tel: (86) 577 68668118
Wechat: zigpac123
Skype: bruce.chan1999
E-mail: bruce@zigpac.com
Whatsapp: +86-18668768846
Telegram: @Zigpacstickers

Company Info
Name: Wenzhou Zigpac Industry Limited
Address: No. 148-152, Building C, Jiangbin Commercial and Residential Building, Longgang City, Wenzhou City, Zhejiang 325802, China

YOUR CUSTOM

PRINTING & PACKAGING **PARTNER** FOR SMALL AND **MEDIUM BUSINESSES**



Die Cut vs Kiss Cut Stickers for Product Labels: Which Cut Fits Your Packaging, Application Speed and Budget?

Details

Quick answer: Zigpac's rule for die cut vs kiss cut stickers on product labels is simple: choose kiss cut when your team or a labeling line applies the labels, and choose die cut when the sticker is handed to customers as a finished piece. A kiss cut goes through the face material and adhesive only, so the backing stays whole and labels peel off one after another. A die cut also goes through the backing, so each sticker leaves with its own shaped liner, and that extra handling usually raises the cost per label. At Zigpac, we confirm the cut type on your quote once you tell us whether the labels will go on by hand or by machine.

Why the Cut Decides How Fast Your Labels Go On

Most brands choose a label cut from a mockup. The rendering looks clean, the shape matches the logo, and the order goes in. The cut method then shows up at the packing table, where it decides how many seconds each label takes, what goes in the bin afterwards, and whether the labels can ever run on a machine.

Public buyer reviews from 2024 to 2026 keep reporting the same cut-related failures. Kiss cuts set too shallow leave half a batch unpeelable. Through-cuts that never reach the liner look finished but will not lift. Shaped singles tear at the inside corners when someone peels them in a hurry. None of these are artwork problems. They come from choosing a cut, or a cut depth, that does not suit how the label is applied.

This guide compares the cut method itself: how deep the blade goes, what stays on the backing, peel speed, backing waste, hand versus machine application, and what drives unit cost. It ends with a decision rule you can apply to any product label.

Contents

1. What is the difference between die cut vs kiss cut stickers?
2. A five-step decision rule for product labels
3. Die cut vs kiss cut product labels compared
4. FAQ
5. Key takeaways
6. Conclusion and next step

What Is the Difference Between Die Cut vs Kiss Cut Stickers?

Every pressure-sensitive label is a stack of three layers: the printed **face stock** (vinyl, paper or film), the **adhesive**, and a silicone-coated **release liner** that keeps the adhesive clean until application. The difference between the two cuts is how many of those layers the blade goes through.

A trade guide for sticker manufacturers puts it in one line: kiss-cutting "cuts through the face stock and adhesive layer while leaving the release liner backing intact," while punch die-cutting "slices through all layers including the backing liner" (eLoveBook Magazine, 2026[1]). A kiss cut therefore cuts 2 of the 3 layers and a die cut cuts all 3.

That one difference determines what you receive:

- **Kiss cut:** the labels sit on one continuous liner, either a sheet or a roll. Each label lifts on its own while the liner holds everything else in place. The unprinted face material between the labels (the "matrix") can be stripped at the factory so label edges stand free, or left on as a border that protects the edges in a stack.
- **Die cut:** each sticker is a separate piece with a liner of the same shape. Nothing connects one sticker to the next.

One terminology trap catches many buyers. In label converting, the cutting tool is called a "die" whichever depth it cuts to, so "die-cut labels on a roll" are almost always kiss-cut on a continuous liner. In the consumer sticker market, "die cut" usually means a fully separated, shaped single. Do not ask a supplier "die or kiss?" Ask: "*Will the liner be cut, or left whole?*" That question has only one possible answer.



How to Pick the Cut for Product Labels: A Five-Step Decision Rule

Step 1: Name who applies the label

This answer settles most of the decision, so start with it.

Your own staff, by hand → kiss cut. When one label is peeled from a sheet, the next one is already in position on the same liner. Nobody has to sort loose pieces, turn them over, or find a liner edge. With the matrix stripped, a fingernail lifts each label edge directly. Sheets also lie flat at a packing

station and are easy to count. For small-batch brands that label jars, pouches or mailers at a table, kiss-cut custom sticker sheets are the default.

A labeling machine → kiss cut on a continuous roll liner. An applicator pulls the liner sharply around a peel edge. The label is stiffer than the liner, so it keeps moving forward, separates, and is pressed onto the product. This only works on an unbroken liner web. Die-cut singles cannot be fed into an applicator, and sheets have to be applied by hand. That is why industrial labeling runs almost entirely on rolls. In Europe, 2025 self-adhesive labelstock consumption reached 7.37 billion m², with paper rolls at 67% and filmic rolls at 30% of demand, while sheets fell from 7% to 3% over two decades (FINAT / Panteia, 2026[2]). At line speed, the liner must also release evenly every time. FINAT publishes separate methods for low-speed release force (FTM 3) and high-speed release at 10–300 m/min (FTM 4), alongside 180° and 90° peel tests at 300 mm/min (FTM 1 and FTM 2) (FINAT test methods[3]). If your line runs fast, ask any supplier which release-force data they can share.

The customer → die cut. When the sticker is the product, for example a thank-you sticker in the parcel or a logo piece for a laptop or bottle, a shaped single with no border looks like a finished object. The customer peels it once, so peel speed hardly matters.



Step 2: Count labels per unit and per shift

If each product takes two or three labels (front, back panel and tamper seal), a kiss-cut sheet can carry one matched set per unit, so staff never mix up designs. Layout and the number of designs per sheet are covered on the kiss-cut sticker sheet page. For the cut decision, one rule is enough: the more labels a person applies per shift, the more a continuous liner saves compared with loose singles.

Step 3: Decide where the backing waste should land

Both cuts start from similar material. They differ in where the waste ends up. With a kiss-cut sheet, the whole liner and any border are left at your packing table, so you bin one sheet per set of labels. With die-cut singles, the waste skeleton is removed at the factory and your customer is left with a liner the size of the sticker. Choose the location that suits your operation: a central bin at the packing

station is easy to manage, while scraps spread across thousands of customer homes are not your problem but are not saved either.

Liner waste is a real operating cost at scale. A label materials product manager quoted in Label & Narrow Web[4] named "environmental sustainability, elimination of waste, and efficiency" as the reasons linerless formats are growing in logistics labeling. Linerless is rarely relevant to branded product labels, but the same logic applies: less liner per label means less to handle and dispose of.

Step 4: Choose the material separately from the cut

The cut does not make a label waterproof or fade-resistant. Face stock, ink and laminate do. A paper label wrinkles once it gets properly wet whichever cut you choose. Laminated vinyl handles condensation, oils and handling much better. For labels on bottles, chilled products or anything stored outdoors, Zigpac's **Premium Custom Die Cut Vinyl Stickers** (weatherproof, UV laminated) are the die-cut option. If kiss-cut labels on a sheet will face the same conditions, specify a laminated vinyl face stock for them too.

If labeled products rub against each other in shipping cartons, ask whether the print has been rub-tested. ISO 18947-1:2021[5] covers general rub testing of prints and references the Sutherland method described in ASTM D5264. For adhesion, the reference methods are ASTM D3330/D3330M (re-approved in 2025) or FINAT FTM 1. A supplier who quotes a method number and a dwell time is giving you something you can check. "Strong adhesive" is not.

Step 5: Peel-test a physical sample before bulk production

Zigpac recommends approving a physical sample before bulk production, and testing it the way your staff will use it. Peel 5–10 labels, taken from the middle and the edges of the sheet, including the smallest shape and any inside corners. Then check for three faults:

- **Cut too shallow:** the face stock tears or stretches, or the label stays attached to the matrix.
- **Cut too deep on a kiss cut:** the liner is scored, so the sheet splits or labels drop off in the box. On a roll, a scored liner can break under applicator tension.
- **Cut off register:** a white sliver on one side, or the blade cutting into the artwork on the other. Keep critical text at least 1/8 in (about 3 mm) inside the cut line.

Die Cut vs Kiss Cut Product Labels Compared Side by Side

At Zigpac, we ask how your labels will be applied, by hand at a packing table or on a labeling line, before we confirm the cut, because that answer narrows the choice faster than any material spec. Use the table to check that decision against your packaging, speed and budget.

Factor	Kiss cut	Die cut
Layers the blade cuts	Face stock + adhesive (2 of 3)	Face stock + adhesive + liner (3 of 3)
What stays on the backing	One continuous liner holding many labels; matrix stripped or left as a border	Nothing shared; each sticker has its own shaped liner
Peel speed for staff	Fast: the next label is already in place; no sorting	Slower: pick up each piece and find the liner edge (a split back liner helps)
Machine application	Yes, when supplied on a continuous roll liner; sheets are hand-applied	No; loose singles cannot be fed into an applicator

Factor	Kiss cut	Die cut
Where backing waste lands	At your packing table: a full liner per sheet	Trimmed at the factory; the end user discards a sticker-sized liner
Main unit-cost drivers	Many labels per cut pass and per handling step	Through-cut plus counting and packing every piece
Typical failure	Depth set too shallow (won't lift) or too deep (liner scored)	Incomplete through-cut; tearing at inside corners
Best product-label use	Labels your team or line applies: jars, pouches, boxes, seals	Stickers handed to customers: parcel inserts, logo pieces
Zigpac option	Custom Kiss-Cut Sticker Sheets	Premium Custom Die Cut Vinyl Stickers (weatherproof, UV laminated)

At Zigpac, both options are quoted with price tiers from 50 pcs, final MOQ on your quote, so you can test either cut at small volume before deciding on a full run.



What actually drives unit cost

Three factors set the price gap between the cuts. The first is depth control: a kiss cut has to stop within the thickness of the face stock and adhesive, so depth is set and checked for each material. The second is handling, which is usually the largest factor. A kiss-cut sheet is counted, stacked and packed as one unit no matter how many labels it carries, while every die-cut single has to be counted, stacked and packed on its own. The third is tooling. Short-run digital work keeps growing: digital and hybrid printing accounts for an average 39.3% of package and label output among surveyed US printers, expected to reach 53.5% within five years, and 45.5% of respondents named custom, short-run digital work as a leading disruptor (PRINTING United Alliance, 2025[6]). Short digital runs are often cut without a dedicated steel die, so a custom shape adds little cost. The number of pieces that have to be handled matters more. To compare cuts fairly, request quotes at the same label size, material and quantity.

Backing waste and recycling claims

Release liners are silicone-coated, and whether a local recycling stream accepts them varies. Before you print "recyclable" on a label or package, remember that the FTC Green Guides at 16 CFR Part 260[7] (§260.12) require substantiation for recyclability claims. In California, SB 343[8] restricts recycling symbols on products and packaging manufactured after October 4, 2026. A federal preliminary injunction issued on July 14, 2026 blocks only enforcement, not the law itself. Labeling programs are moving the same way: How2Recycle's director told Waste Dive[9] that standards "are going beyond technical recyclability." Neither cut makes a label recyclable, so base any claim on the specific face stock, adhesive and liner.



FAQ: Die Cut vs Kiss Cut Stickers

FAQ: Are kiss cut stickers faster to peel than die cut stickers?

Yes, for anyone applying many labels in a row. The labels stay on one continuous liner, so the next label is already in place and nothing has to be sorted. With the matrix stripped, each edge lifts with a fingernail. Die-cut singles are peeled once by the end user, so their peel speed rarely matters.

FAQ: Can die cut stickers run on a labeling machine?

No, not as loose singles. An applicator needs an unbroken liner web to pull around its peel edge, so machine-applied labels are supplied kiss-cut on a continuous roll. Sheets are designed for hand application.

FAQ: Which cut costs less per label?

Kiss cut usually costs less per label, because many labels share one cut pass and one handling step. Die-cut singles add counting and packing for every piece. The only fair comparison is a pair of quotes at the same size, material and quantity.

FAQ: Does kiss cutting create more backing waste?

It moves the waste rather than adding to it. With a kiss-cut sheet, the whole liner is left at your packing table. With a die cut, the skeleton is trimmed at the factory and the end user throws away a small shaped liner. If you plan to make recycling claims, check the face stock, adhesive and liner against 16 CFR Part 260 and, for California, SB 343.

FAQ: Can I order both cuts from Zigpac?

Yes. Zigpac offers Custom Kiss-Cut Sticker Sheets for labels your team applies and Premium Custom Die Cut Vinyl Stickers (weatherproof, UV laminated) for stickers handed to customers, both with price tiers from 50 pcs, final MOQ on your quote. Tell us how the labels will be applied and Zigpac confirms the cut type on the quote.

FAQ: Does the cut make a label waterproof?

No. Water, oil and UV resistance come from the face stock, ink and laminate, not from the cut. Choose laminated vinyl for wet, chilled or outdoor products with either cut, and keep paper labels for dry, indoor use.

Key Takeaways

- **A kiss cut leaves the liner whole; a die cut goes through it.** — 2 of 3 layers cut versus 3 of 3 (Source)
- **Machine labeling runs on kiss-cut rolls, not sheets or singles.** — rolls made up 97% of European labelstock demand in 2025 (67% paper + 30% film); sheets 3% (Source)
- **Release force matters at line speed.** — FINAT FTM 4 tests high-speed release at 10–300 m/min (Source)
- **Short-run digital work keeps custom shapes affordable, so handling drives the cost gap.** — digital share of output 39.3% today, 53.5% expected within five years (Source)
- **Recycling claims on labels need substantiation in California and federally.** — SB 343 covers items manufactured after October 4, 2026; enforcement paused July 14, 2026 (Source)
- **You can test either cut at small volume.** — price tiers from 50 pcs, final MOQ on your quote (Source)

Conclusion: Let the Application Method Pick the Cut

Choosing between die cut and kiss cut is mostly a question of who peels the label. If your team or a labeling line applies it, kiss cut keeps the liner continuous, speeds up peeling and handles at lower cost. If the sticker goes home with a customer as a finished piece, die cut gives a clean shaped object. Choose material for the environment the label will face, peel-test a physical sample, and keep recycling claims tied to the actual liner and face stock.

To get a quote, send your artwork, label size, quantity, and whether the labels will be applied by hand or on a labeling line. Zigpac confirms the cut type and the final MOQ on the quote. If your team will apply the labels by hand, start with our Custom Kiss-Cut Sticker Sheets.

References

1. eLoveBook Magazine, "A Manufacturer's Guide to Producing Custom Printed Stickers,"

2026-09-09. https://elovebook.com/a-manufacturers-guide-to-producing-custom-printed-stickers/ ↩
2. FINAT, "European Label Forum 2026: Label industry moves from recovery to strategic repositioning" (Panteia data, 2025 consumption), published May 2026. https://www.finat.com/news/finat-european-label-forum-2026-label-industry-moves-from-recovery-to-strategic-repositioning ↩
3. FINAT, Test Methods directory (FTM 1–5), accessed 2026-10. https://www.finat.com/resources/finat-test-methods/ ↩
4. Label & Narrow Web, "Avery Dennison chronicles growth in linerless labeling," 2025-11-21. https://www.labelandnarrowweb.com/exclusives/avery-dennison-chronicles-growth-in-linerless-labeling/ ↩
5. ISO 18947-1:2021, Imaging materials and prints — Abrasion resistance — Part 1: General rub testing methods. https://www.iso.org/obp/ui/fr?_escaped_fragment_=iso:std:75677:en ↩
6. PRINTING United Alliance, "State of the Package and Label Printing Industry, Fall 2025, Executive Summary." https://www.printing.org/docs/default-source/research-docs---public/pbos_package_and_label_printing_industry_fall_2025_executive_summary.pdf ↩
7. Electronic Code of Federal Regulations, 16 CFR Part 260, Guides for the Use of Environmental Marketing Claims, current as of 2026-10. https://www.ecfr.gov/current/title-16/chapter-I/subchapter-B/part-260?toc=1 ↩
8. CalRecycle, "SB 343: Accurate Recycling Labels" (FAQ 2025-08-13; injunction note 2026-07-14). https://calrecycle.ca.gov/wcs/recyclinglabels/ ↩
9. Waste Dive, How2Recycle recyclability label changes and SB 343, 2026-10-14. https://www.wastedive.com/news/how2recycle-recyclability-label-sb343-mrf-acceptance/803712/ ↩

November 24, 2026